



Highlights

- Two 1 Gbps iSCSI host connections, and one 3 Gbps SAS drive interface for capacity expansion, per controller
 - Affordable, reliable IP networked-attached storage
 - Combination of 12 SAS—up to 7.2 TB—or SATA—up to 24.0 TB—drives per enclosure
 - Expandable to 28.8 TB with SAS or up to 96.0 TB SATA with up to three EXP3000 enclosures
 - Solution for IBM System x®, IBM BladeCenter®, and select third-party servers
 - Network Equipment-Building System (NEBS) and European Telecommunications Standards Institute (ETSI) compliance
-

IBM System Storage DS3300 Express

Low-cost IP SAN storage solution for consolidation, single management and increased efficiencies

With the proliferation of servers and the influx of data growth in today's IT environments, organizations from a small-to-medium business to the enterprise understand the value that networking plays in managing applications and business data. Today, the connectivity of storage devices must enable substantially higher scalability, availability and manageability than is possible with direct attached storage (DAS). To use data to its fullest extent, it must be accessible to those who need it. Consolidating data by means of a network is the best way to achieve this.

The IBM System Storage® DS3300 Express is designed to meet the availability and consolidation needs for a wide range of users—from the entry-level SMB to an enterprise's remote site or departments. The DS3300 provides organizations an affordable, reliable and scalable storage solution that takes advantage of their current Internet Protocol (IP) infrastructure equipment and in-house expertise.

Easy to deploy and manage

The IBM System Storage DS3000 Storage Manager software is designed to provide a friendly user interface from setup to administration. Its task-based user interface significantly reduces the complexity of installation, configuration and management. The DS3000 Storage Manager approach is designed to enable even non-storage savvy administrators to quickly set up and deploy their storage solution.



The iSCSI host interface technology used by DS3300 is mature and has a broad range of proven management tools. It can often be simply administered in-house as networking expertise is common throughout many companies today. This can help organizations capitalize on their existing IT skill sets and avoid having to learn a new networking protocol, which can include extensive training. With the DS3300 Express storage system, transitioning DAS configurations to an IP Storage Area Network (SAN) is a simple task for even the most inexperienced full-time administrator.

Tiered storage solution

Tiered storage is the assignment of different categories of data to different types of drives in order to reduce total storage cost. A key attribute of the DS3300 Express is the integration of SAS and SATA technologies within a single enclosure. This simplifies purchasing and storage deployment with nearline applications using inexpensive SATA drives and highly-utilized applications deploying SAS drives.

Expand with multiple EXP3000s

The scalability of the DS3300 Express helps IT managers respond to their constantly changing storage environment. By starting small, the DS3300 Express enables users to make additional investments in their infrastructure only when they need it. The DS3300 Express capacity is increased either by adding hard disk drives or additional EXP3000 Express expansion units. Both of these operations can be performed without having to shut down the system. This means 'zero impact' and gives users control of their data storage as they scale their capacity on an as-needed basis.

Extensive reach

The reach of a SAN throughout the organization is most often limited by the distance restriction of the fabric. As a routable transport with virtually no distance limitations, the DS3300 Express can be located almost anywhere. iSCSI



IBM System Storage DS3300 Express

breaks through any distance limitations and can extend its scope to remote locations well beyond the corporate data center.

Flexible approach to storage

The DS3300 Express is a comprehensive storage solution for IBM System x, IBM BladeCenter and select third-party servers. This flexibility helps free organizations from server barriers by offering a single storage solution in a mixed-vendor environment. And because functionality is not sacrificed for affordability, the DS3300 Express disk storage system can deliver powerful capabilities that further help protect data. The DS3300 Express enables optional copy and disaster recovery (DR) features such as IBM FlashCopy and Volume Copy that can be enabled when an application necessitates it.

Reduce IT expenditures

In addition to leveraging low-cost IP network equipment, the DS3300 Express was designed to be an affordable and easy-to-manage storage system. By configuring an IP SAN, a user can avoid the investment of completely retrofitting their existing network, allowing organizations to capitalize on their existing IP network equipment. And when existing equipment is not available, the cost of new IP components is relatively low, ensuring that future growth expenditures will not break the budget.

IBM System Storage DS3300 Express at a glance

Models	1726-31X—single controller 1726-32X—dual controller
RAID controller	Dual active
Cache per controller	512 MB battery-backed cache with 1 GB upgrade option
Host interface	Two host ports per controller, 1 Gbps iSCSI
Drive interface	Serial Attached SCSI (SAS)
Supported drives	3 Gbps SAS: 146 GB, 300 GB, and 450 GB SAS drives at 15,000 rpm speeds 6 Gbps SAS: 300 GB, 450 GB, 600 GB SAS drives at 15,000 rpm speeds 3 Gbps SATA: 500 GB, 750 GB, 1.0 TB, 2.0 TB SATA drives at 7,200 rpm speed
RAID levels	RAID 0, 1, 3, 5, 6, 10
Storage partitions	4, 8, 16, 32
Maximum drives supported	48 SAS or SATA drives (using three EXP3000 expansion units)
Fans and power supplies	Dual-redundant, hot-swappable
Rack support	19" industry-standard rack
Management software	IBM System Storage DS3000 Storage Manager
Warranty¹	Three-year parts and labor
Size	Height: 8.7 cm (3.4 in) Depth: 55.0 cm (21.6 in) Width: 44.7 cm (17.6 in) Weight: approximately 17.2 kg (38.0 lb) for a standard unit; when fully configured, 29.2 kg (64.5 lb)
Environment	Air temperature: – DS3300 on: 10° to 35°C (50.0° to 95°F); altitude: 30.5 m (100 ft) below to 3000 m (9840 ft) above sea level; temperature change: 10°C (18°F) per hour – DS3300 off: 10° to 50°C (14.0° to 120.0°F); maximum altitude: 3000 m (9840 ft); temperature change: 15°C (27.0°F) per hour Humidity: – DS3300 on: 20 to 80 percent – DS3300 off: 10 to 90 percent – Maximum dew point: 26°C (79°F) – Maximum humidity gradient: 10 percent per hour
Heat output	Approximate heat output in British thermal units (Btu) per hour: – Minimum configuration: 205 Btu (60 watts) – Maximum configuration: 1235 Btu (361 watts)
Supported systems	For a list of currently supported servers, operating systems, host bus adapters, clustering applications, SAN switches and directors, refer to the DS3000 Express series Interoperability matrix available at ibm.com/systems/storage/disk/ds3000/ds3300/

For more information

To learn more about the [IBM System Storage DS3300 Express](#), please contact your IBM representative or IBM Business Partner, or visit:

- ibm.com/systems/storage/disk
- ibm.com/systems/x
- ibm.com/systems/bladecenter

Additionally, IBM Global Financing can tailor financing solutions to your specific IT needs. For more information on great rates, flexible payment plans and loans, and asset buyback and disposal, visit: ibm.com/financing



© Copyright IBM Corporation 2010

IBM Systems and Technology Group
Route 100
Somers, New York 10589

Produced in the United States of America
April 2010
All Rights Reserved

IBM, the IBM logo, ibm.com, and System Storage are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at ibm.com/legal/copytrade.shtml.

Other company, product, or service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.

¹ IBM hardware products are made from new parts, or new and serviceable used parts. Regardless, our warranty terms apply. For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services including those designated as ServerProven® or ClusterProven.



Please Recycle
